



12 Volt Belt Feeder



Capacity Approximately 12kg

Operation Programmable 12, 18, 24 and 48 hour operation on same feeder, with automatic cut off when completed. LEDs give indication of selected time program and when feeder has fully paid out or stopped.

Power supply 12 volts dc

Power consumption 0.1 amp

Materials PE, PVC, 316 SS, Brass

Dimensions (external) 590 x 395 x 250mm deep

Installation min 0.5mm twin core cable. Feeders connected in parallel.

IP Rating IP66 (AD6/AE6)

Power supplies Feeders can either be supplied by stand alone 12 volt batteries (typical 120Ah battery will allow 10 feeders to run for 2 weeks) or preferably through a charger/ battery set. Power sets include time-switch to start feeding at preset time.

| Item | Order code |
|--|------------|
| Feeder | BF001 |
| Power set for 20 feeders* | BF5103/12 |
| Power set for 40 feeders* | BF5105/12 |
| Power set for 60 feeders* | BF5110/12 |
| IP67 Junction box, fuse link and gland set | BF101 |
| IP55 Junction box and fuse link | BF102 |

*NOTE POWER SETS DO NOT INCLUDE BATTERIES

Warranty 12 months

Patent Applied for 2004, All Rights Reserved Registered Design ®